

정밀급 열전대 와이어

Thermocouple Wire



K-12-TE
T-12-TE



T-25-TE
K-25-TE



K-25-GL
K-50-HGL

SPECIFICATION

Model	Type	Wire Dia (AWG)	Insulation	Max Temp (Insulation)	Overall size
T-25-TE	T	0.25mm (30AWG)	FEP Teflon	230 °C	0.76x1.27mm
K-25-TE	K	0.25mm (30AWG)	FEP Teflon	230 °C	0.76x1.27mm
T-12-TE	T	0.12mm (36AWG)	PFA Teflon	205 °C	0.43x0.71mm
K-12-TE	K	0.12mm (36AWG)	PFA Teflon	205 °C	0.43x0.71mm
K-25-GL	K	0.25mm (30AWG)	Fiberglass	520 °C	0.76x1.22mm
K-50-HGL	K	0.51mm (24AWG)	High fiberglass	850 °C	1.83x3.05mm

General Specification

- Class : Special ($\pm 0.4\%$)
- Length : 1000ft (300m) / Roll

(주)대현테크놀로지

경기도 성남시 중원구 사기막골로 124 SK 테크노파크 비즈센터 1013호

T 031-776-2525 / www.dhtc.co.kr / dhtc@dhtc.co.kr